



THIS DESIGN AND INFORMATION CONTAINED ON THIS PRINT IS THE PROPERTY OF VALLEY FAB CORPORATION. ANY REPRODUCTION, DUPLICATION OR TRANSFER OF THE PROPRIETARY CONTENT IS PROHIBITED WITHOUT WRITTEN PERMISSION.

STANDARD TOLERANCES:

(UNLESS OTHERWISE NOTED)
 FRACTIONS - 1/16"
 DECIMALS - 0.01"
 ANGLES - 0.5°

NEWAVE
 TOWER COMPONENTS. 503-792-3739
 10910 PORTLAND RD. BROOKS, OR 97305

TOTAL WT: 10.55 LB

QTY:

FINISH: HDG

JOB #:

| ITEM | PART # | QTY | DESCRIPTION | LENGTH | FINISH | UNIT WT |
|-------------------------|--------------|-----|---|--------|--------------|-----------------|
| 1 | WB5026-24.01 | 1 | 24" ADJUSTABLE SPLICE, 45 DEG. | | | 10.02 |
| 2 | 27-5050-005 | 6 | GALV. 3/8" x 1" GR.5 BOLT | | | 0.05 |
| 3 | 27-5010-005 | 3 | GALV. 3/8" FLAT WASHER | | HDG | 0.02 |
| 4 | 27-5020-005 | 6 | 3/8" HDG LOCK WASHER | | | 0.01 |
| 5 | 27-5030-005 | 6 | 3/8" HDG HEX NUT | | | 0.02 |
| TITLE: | | | SOLID WAVEGUIDE BRIDGE, 24" ADJ. SPLICE, ROTATE UP TO 45 DEG. | | DRAWN BY: JG | DATE: 7/17/2018 |
| SERIES: COAX ICE BRIDGE | | | SHEET: 1 OF 1 | | CHK'D BY: | |
| | | | | | | WB5026-24 |